

**Mobile Rail Cutter RC26R**  
for carriers from 35,000 to 75,000 lbs.



***The Mobile Rail Cutter RC 26 R was developed for the efficient and controlled demolition of rail and the scrap preparation of railway lines.***

Rails can be cut into any desired length, such as blast furnace sizes.

To achieve optimal work efficiency, the Mobile Rail Cutter should be mounted on the dipper stick of an excavator. Optimal working efficiency is guaranteed by the high stress-resistant rotation system with a 180° swivel range. The rail cutter quickly and easily reaches every working location required by the job.

**RC 26R Mobile Rail Cutter**

**Specifications:**

<b>Approx. weight excluding mounting bracket</b>	2.600 kg / 5,720 lbs
<b>Length</b>	2.550 mm / 100.4 in
<b>Jaw depth</b>	205 mm / 8.07 in
<b>Cutter length</b>	182 mm / 7.17 in
<b>Jaw opening</b>	205 mm / 8.07 in
<b>Hydraulic cylinder recommended oil flow*</b>	250-350 l/min / 66.7-93.3 gpm
<b>Hydraulic cylinder maximum working pressure</b>	350 bar / 4,550 psi
<b>Rotation recommended oil flow</b>	18-25 l/min / 4.8-6.7 gpm
<b>Rotation maximum working pressure</b>	200 bar / 2,840 psi
<b>Rotation swivel</b>	180°
<b>Approx. excavator size (rail cutter mounted on dipper stick)</b>	16-26 t / 35,200-57,200 lbs

**\*Working cycle times in seconds:**

<b>Oil flow</b>	<b>Close</b>	<b>Open</b>	<b>Total</b>
250 l/min / 66.7 gpm	4.1	2.1	6.2
300 l/min / 80.0 gpm	3.5	1.8	5.3
350 l/min / 93.3 gpm	3.0	1.5	4.5

TRAMAC CORPORATION reserves the right to change or discontinue models and/or specifications without prior notice.

**Muscle Mate is a Tramac Corporation brand.**

**USA:** 12 Orben Drive #3 / Landing, NJ 07850 / 1-800-526-3837 / 1-973-770-4457 / FAX 1-973-770-0812  
**Canada:** 3421 boul. Industriel / Laval, QC / Canada H7L 4S3 / 1-888-663-8122 / 1-450-663-8122 / FAX 1-450-663-6797  
 e-mail: sales@tramac.com http://www.tramac.com

